

C15

IC-PNEUMATIC LPG/DIESEL
 3000 / 3500 / 4000 lbs.
 (1500 / 1800 / 2000 kg)

GEN2



STANDARD SPECIFICATIONS

C15/18/20s

Manufacturer's Designation		C15L	C18L	C20sL	C15D	C18D	C20sD
Load Capacity / Rated Load	lbs(kg)	3000 (1500)	3500 (1800)	4000 (2000)	3000 (1500)	3500 (1800)	4000 (2000)
Height Overhead Guard	in(mm)	83.5 (2120)	83.5 (2120)	83.5 (2120)	83.5 (2120)	83.5 (2120)	83.5 (2120)
Width	in(mm)	42.1 (1070)	42.1 (1070)	42.1 (1070)	42.1 (1070)	42.1 (1070)	42.1 (1070)
Right Angle Stack (add load length and clearance)	in(mm)	97.0 (2465)	98.9 (2513)	100.2 (2546)	97.0 (2465)	98.9 (2513)	100.2 (2546)
Outside Turning Radius	in(mm)	81.6 (2073)	83.5 (2121)	84.8 (2154)	81.6 (2073)	83.5 (2121)	84.8 (2154)
Travel speed loaded / unloaded	mph (kph)	13.3 / 13.5 (21.4 / 21.7)	13.3 / 13.5 (21.4 / 21.7)	13.3 / 13.5 (21.4 / 21.7)	10.7 / 11.1 (17.2 / 17.9)	10.9 / 11.1 (17.6 / 17.9)	10.8 / 11.2 (17.4 / 18.1)
Engine / Rated output per SAE J1349	HP(KW) @ rpm	Hyundai / 52 (38.8) @2650	Hyundai / 52 (38.8) @2650	Hyundai / 52 (38.8) @2650	Yanmar / 38.6 (28.8) @ 2400	Yanmar / 38.6 (28.8) @ 2400	Yanmar / 38.6 (28.8) @ 2400

STANDARD FEATURES

2.4 liter LPG engine or • 2.2 liter Diesel engine • EPA compliant • Electronic governor • Fuel system diagnostics
• Low LPG warning light • Standard, Triple and Hi-lo uprights • Full range of lift heights available • High
visibility “silent staging” uprights • Automatic engine shutdown protection • Two-pedal inch-brake system •
High capacity cooling system • Auxiliary valve • Routine maintenance points are highly accessible • Isolated
operator cell • CLARK safety seat • Tilt steering wheel • LED Instrument display with audible alarms • Full
access clamshell hood / quick removable floorboards • Headlights - overhead guard mounted • Tie-downs
• Automatic engine shutdown feature • Wide range of options are available for the chassis, upright, and
operator compartment



For more information on this model and the full line of CLARK Forklifts, find you local CLARK Dealer at www.clarkmhc.com.