

CQ

IC-PNEUMATIC LPG/DIESEL
 4000 / 5000 / 6000 lbs.
 (2000 / 2500 / 3000 kg)



STANDARD SPECIFICATIONS

20/25/30

Manufacturer's Designation		CQ20D	CQ25D	CQ30D	CQ20L	CQ25L	CQ30L
Load Capacity / Rated Load	lbs(kg)	4000 (2000)	5000 (2500)	6000 (3000)	4000 (2000)	5000 (2500)	6000 (3000)
Height Overhead Guard	in(mm)	83.9 (2130)	83.9 (2130)	83.9 (2130)	83.9 (2130)	83.9 (2130)	83.9 (2130)
Width	in(mm)	47.6 (1210)	47.6 (1210)	49.2 (1250)	47.6 (1210)	47.6 (1210)	49.2 (1250)
Right Angle Stack (add load length and clearance)	in(mm)	109.6(2783)	109.6(2783)	111.1 (2821)	109.6(2783)	109.6(2783)	111.1 (2821)
Outside Turning Radius	in(mm)	91.8(2331)	91.8(2331)	92.9(2359)	91.8(2331)	91.8(2331)	92.9(2359)
Travel speed loaded / unloaded	mph (kph)	12.1 / 12.3 (19.5 / 19.8)	12.0 / 12.3 (19.4 / 19.8)	12.4 / 12.7 (20.0 / 20.5)	12.6 / 12.9 (20.3 / 20.8)	12.5 / 12.9 (20.1 / 20.8)	12.9 / 13.3 (20.8 / 21.4)
Engine / Rated output per SAE J1349	HP(KW) @ rpm	Yanmar 4TNE98 58.6 (43.6) @ 2300	Yanmar 4TNE98 58.6 (43.6) @ 2300	Yanmar 4TNE98 58.6 (43.6) @ 2300	Hyundai Theta 2.4 70.4 (62.5) @ 2650	Hyundai Theta 2.4 70.4 (62.5) @ 2650	Hyundai Theta 2.4 70.4 (62.5) @ 2650

STANDARD FEATURES

Sideshifter, internal hosing and full light package included • Standard, full free lift Triple & HiLo uprights • Isolated operator cell • Full access clamshell hood • Smooth 2.4 liter OHC LPG engine • Optional 2.8 Liter Yanmar Diesel Engine with Vertical Exhaust • Two-pedal inch-brake system • Proven tough, CLARK TA 18 electric shift transaxle • Clark safety seat



For more information on this model and the full line of CLARK Forklifts, find you local CLARK Dealer at www.clarkmhc.com.