

CTX

3-WHEEL TOW TRACTOR
ELECTRIC 48 VOLT
8800 / 15,400 lbs. (4000 / 7000 kg)



STANDARD SPECIFICATIONS

40/70

Manufacturer's Designation		CTX 40	CTX 70
Rolling Load Capacity	lbs(kg)	8800 (4000)	15400 (7000)
Width over Frame	in(mm)	39.2 (995)	39.2 (995)
Height (w/ Weather Enclosure)	in(mm)	80.1 (2035)	80.1 (2035)
Inside Turning Radius	in(mm)	21.7 (550)	21.7 (550)
Travel speed loaded / unloaded	mph (kph)	5.6 (9) / 8.1 (13)	4.3 (7) / 10.6 (17)
Wheelbase	in(mm)	45.6 (1160)	45.6 (1160)
Ground Clearance	in(mm)	3.54 (90)	3.54 (90)

STANDARD FEATURES

Solid pneumatic tires for indoor/outdoor operation • Enclosed motors • 100% AC Motors • Heavy duty drive motors & axles • Regenerative braking • Fully adjustable, full-suspension seat • Fully programmable • Reinforced all steel frame • Optional weather enclosure • Easily serviceable • Tilt steering • Automotive style pedals & dash



For more information on this model and the full line of CLARK Forklifts, find you local CLARK Dealer at www.clarkmhc.com.